



- Dimension: 150*81.5*40.3mm
- Application: for PC
- Watt:220W
- PFC: Active

Feathers :

- For Intel SFX12V Ver1.0, output :220W(300W Max)
- AC input full range
- High efficiency
- Low ripple & noise
- Output over voltage protection
- Short circuit protection on all outputs
- Internal 4CM FAN
- 100% burn-in under high ambient temperature(50°C)
- MTBF:80K hours at 25°C

DC Connectors :



20+4P for M/B



4Pin for CPU



4Pin for HDD



4Pin for FDD

Input Specifications :

- AC INPUT:100-240V
- Frequency:47-63Hz
- Current:4A @100-240Vac 60Hz/ 50Hz

Output Specification :

- Maximum Power: 220W
- Color: Silver
- Cooling System: SPEED: 9000RMP(+/-10%)
DIMENSION:81.5*150*43mm
TEMP.AUTO ONTROL:
2200rpm at 41.7°C~8000rpm at 60.5°C
4CM Fan
- Noise: 22dB at 8000rpm
- P.G Signal:100-500ms
- Hold-up Time:17ms(min)
- Efficiency:75%

Output :

Output Voltage	Min. load	Max. load	Load Reg.	Ripple & Noise
-12V	0.0A	0.5A	±10%	120mV P-P
+3.3V	0.1A	13.0A	±5%	50mV P-P
+5V	0.2A	14.0A	±5%	50mV P-P
+5Vsb	0.0A	2.0A	±5%	50mV P-P
+12V	0.6A	14.0A	±5%	120mV P-P

- +3.3V & +5V total output shall not exceed 80W.
- +3.3V & +5V & +12V1 total output shall not exceed 205W
- * Detailed specifications and drawings provided upon request.